

Product Overview

The Vykon HVAC range of I/O modules are designed for use as local I/O within motor control cabinets or as remote I/O connected via RS485 Modbus.

The Vykon HVAC 4AOH-3DO module provides 4 independent analogue output channels with hand-auto override switches and setting potentiometers. Each output has a yellow LED. The module also provides 3 independent 240vac/8A rated digital relay output channels each with change over contact configuration.

The IP20 rated module may be plugged together with other modules on standard TS35 DIN rail or direct mounting; the cascable design allows power and 2-wire RS485 Modbus communications to connect through without any extra wiring.

Modbus address setting is by rotary switches which are easily accessible underneath the top cover. A bi-colour LED indicates the communications status.

Connectivity

The 4AOH-3DO module has one 2-wire RS485 port supporting a Modbus communications network connection to the JACE® controller.

Engineering

Configuration and engineering of the 4AOH-3DO module is performed using Vykon HVAC.

Typical applications

Typical applications include building automation control systems.

Vykon HVAC A & D output module 4AOH-3DO DATA SHEET

Analogue & digital output module 4 analogue & 3 digital outputs

DATA SHEET



Features

- 4 analogue outputs 0 to 10vdc
- Hand-auto override switches and setting potentiometer on each analogue output
- 3 digital outputs with change over contacts
- DIN rail or direct mounting
- 24V ac or dc power operation
- Supports RS485 2-wire Modbus Open Communication network
- Easy address setting using rotary switches
- Bi-colour LED for module status information
- Yellow LED indication per analogue output

Vykon HVAC A & D output module 4 analogue & 3 digital outputs

Ordering information: VY- 4AOH-3DO

Analogue output data:

number of outputs	4
output range	0v to 10v dc
load resistance per channel	>1,000 Ω
maximum load current per channel	<10ma
resolution	10mv
conversion error	± (30mv + 0.5%)
temperature coefficient	0.01%/°C

Digital output data:

number of outputs	3
rated switching voltage	240v ac
rated / inrush current (resistive load)	8A / 12A
maximum power rating	2,000VA
maximum total module current	24A
electrical life expectancy at rated / 2A load	>1 x 10 ⁵ cycles / > 4 x 10 ⁵ cycles
mechanical life expectancy	> 5 x 10 ⁶ cycles
maximum switching frequency	6 min ⁻¹ at rated current; 1,200 min ⁻¹ at no load
contact material	AgNi
isolation test voltage (coil to contact)	4 kV
output relay contact configuration	channels 1,2 & 3: change over contacts;

LED status indication:

per analogue output	yellow: intensity relative to output voltage; V<1.5v=off
per digital input	bi-colour: red; green or off. status: normal or inverted
module status	bi-colour: green-normal operation; blinking red-communications error

Bus data:

bus protocol	Modbus RTU
bus interface	RS485, half duplex, non isolated
bus topology	multidrop
bus length maximum	500m
bus nodes maximum	64
bus speed	19,200 bps
bus line termination	integrated termination resistors, activate via jumper (default: off)
bus protection	built-in transient protection
bus connector	pluggable male & female integrated connectors (modules mounted with zero spacing)
bus split connector (not included)	pluggable male or female screw connector. 0.2mm ² to 1.0mm ² insulation stripping length 7mm
bus cabling	twisted pair (use STP in industrial environments)

General data:

module power supply	20v to 28v ac or dc
module current	75ma ac or 30ma dc
protection circuit	reverse power supply voltage protection
operating temperature range	0°C to +50°C
storage temperature range	-20°C to +70°C
DIN-VDE regulations	DIN-EN 50178: 1997 / DIN-VDE 0110 pollution degree 2, over voltage category III
electromagnetic compatibility	CE in compliance
conductor cross section	0.2mm ² to 1.5mm ² screw clamp connection
insulation stripping length	6mm
mounting	DIN-rail TS35 (35mm x 7.5mm) or direct mounting by M3 fixing
installation position	any
assembly	up to 15 in a row with zero spacing
module size (l x w x h)	53mm x 95mm x 60mm
isolating material / flammability class	Housing: Noryl. Terminals: Polyamid 6.6 V0 / UL94-V0
protection degree (DIN 40050)	IP 20

